

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML**

Article number: 071010

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category Paint remover

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Preparation

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

European Aerosols B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel : +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

Further information obtainable from: Department Product Safety

1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

IRL: Beaumont Hospital - National Poisons Information Centre: Tel: +353 1 8092566

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML**

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** *Danger*· **Hazard-determining components of labelling:**

acetone
 n-butyl acetate
 2-methoxy-1-methylethyl acetate
 butan-1-ol

· **Hazard statements**

H222-H229 *Extremely flammable aerosol. Pressurised container: May burst if heated.*
 H319 *Causes serious eye irritation.*
 H336 *May cause drowsiness or dizziness.*

· **Precautionary statements**

P101 *If medical advice is needed, have product container or label at hand.*
 P102 *Keep out of reach of children.*
 P210 *Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.*
 P211 *Do not spray on an open flame or other ignition source.*
 P251 *Do not pierce or burn, even after use.*
 P260 *Do not breathe spray.*
 P410+P412 *Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.*
 P501 *Dispose of contents / container in accordance with regional regulations.*

· **Additional information:**

EUH066 *Repeated exposure may cause skin dryness or cracking.*
Buildup of explosive mixtures possible without sufficient ventilation.
 EUH211 *Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.*

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**· **Description:** Mixture of substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	25-<50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	20-<25%

(Contd. on page 3)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 2)

CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	12.5-<20%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336	5-<10%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32	butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27	isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280	5-<10%
CAS: 9004-70-0	cellulose nitrate ⚠ Expl. 1.1, H201	2.5-<5%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol ⚠ Flam. Liq. 3, H226 ⚠ Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	≥1-<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ⚠ Carc. 2, H351	≥1-<2.5%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	propan-2-ol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319; STOT SE 3, H336	<2.5%

• **Additional information:**

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• **4.1 Description of first aid measures**

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:** Generally the product does not irritate the skin.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 3)

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm
	Long-term value: 1210 mg/m ³ , 500 ppm

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm
	Long-term value: 766 mg/m ³ , 400 ppm

(Contd. on page 5)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: **PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML**

(Contd. of page 4)

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm
Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

71-36-3 butan-1-ol

WEL Short-term value: 154 mg/m³, 50 ppm
Sk

13463-67-7 titanium dioxide

WEL Long-term value: 10* 4** mg/m³
*total inhalable **respirable

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm
Long-term value: 999 mg/m³, 400 ppm

· DNELs**67-64-1 acetone**

Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
	DNEL	186 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	2420 mg/m ³ (Worker, acute local)
	DNEL	1210 mg/m ³ (Worker, longterm systemic)
	DNEL	200 mg/m ³ (Consumer, longterm systemic)
	DNEL	60 mg/m ³

123-86-4 n-butyl acetate

Oral	DNEL	2 mg/kg /per day (Consumer, longterm systemic)
	DNEL	2 mg/kg /per day (Consumer, acute systemic)
Dermal	DNEL	11 mg/kg /per day (Worker, longterm systemic)
	DNEL	11 mg/kg /per day (Worker, acute systemic)
	DNEL	6 mg/kg /per day (Consumer, longterm systemic)
	DNEL	6 mg/kg /per day (Consumer, acute systemic)
Inhalative	DNEL	300 mg/m ³ (Worker, longterm systemic)
	DNEL	600 mg/m ³ (Worker, acute systemic)
	DNEL	300 mg/m ³ (Worker, longterm local)
	DNEL	600 mg/m ³ (Worker, acute local)
	DNEL	35.7 mg/m ³ (Consumer, longterm systemic)
	DNEL	300 mg/m ³ (Consumer; acute systemic)
	DNEL	35.7 mg/m ³ (Consumer, longterm local)

108-65-6 2-methoxy-1-methylethyl acetate

Dermal	DNEL	796 mg/kg /per day (Worker, longterm systemic)
	DNEL	320 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	275 mg/m ³ (Worker, longterm systemic)

(Contd. on page 6)

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 6)

PNEC	140.9 mg/l (Seawater)
PNEC	140.9 mg/l (Sporadic release)
PNEC	2251 mg/l (Sewage treatment plant)
PNEC	552 mg/kg (Freshwater sediment)
PNEC	552 mg/kg (Seawater sediment)

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see section 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· **Respiratory protection:**



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Physical state**

Aerosol

(Contd. on page 8)

GB

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 7)

· Colour:	Black
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-butyl acetate)
· Upper:	26.2 Vol % (115-10-6 dimethyl ether)
· Flash point:	Not applicable, as aerosol.
· Auto-ignition temperature:	240 °C (464 °F) (115-10-6 dimethyl ether)
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	4000 hPa (3000.2 mm Hg)
· Density and/or relative density	
· Density at 20 °C (68 °F):	0.8 g/cm ³ (6.7 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Not determined.
· Solvent content:	
· Organic solvents:	90.5 %
· Water:	0.3 %
· VOC (EC)	---
	693.9 g/l
· VOC-EU%	90.54 %
· Solids content:	8.9 %
· Change in condition	
· Evaporation rate	Not applicable.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void

(Contd. on page 9)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 8)

- | | |
|----------------------------------|------|
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
	LC50 / 96 h	5540 mg/l (oncorhynchus mykiss)

123-86-4 n-butyl acetate

Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>21 mg/m ³ (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50 / 4 h	>10000 mg/m ³ (rat)

71-36-3 butan-1-ol

Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4 h	17000 mg/m ³ (rat)

67-63-0 propan-2-ol

Oral	LD50	5840 mg/kg (rat)
Dermal	LD50	13900 mg/kg (rabbit)
Inhalative	LC50	>25 mg/l (rat)
		LC 50: 6h

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 10)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 9)

· **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

67-64-1 acetone

LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))

115-10-6 dimethyl ether

EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)

108-65-6 2-methoxy-1-methylethyl acetate

EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss)

71-36-3 butan-1-ol

LC50 / 96 h	1376 mg/l (fish)
-------------	------------------

67-63-0 propan-2-ol

LC50/96h	9640 mg/l (pimephales promelas; 96h)
LC50 / 24 h	9714 mg/l (daphnia magna)

· **12.2 Persistence and degradability** No further relevant information available.

· **12.3 Bioaccumulative potential** No further relevant information available.

· **12.4 Mobility in soil** No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

(Contd. on page 11)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022



Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

Disposal must be made according to official regulations.

(Contd. of page 10)

*

SECTION 14: Transport information

· 14.1 UN number or ID number	UN1950
· ADR, IMDG, IATA	
· 14.2 UN proper shipping name	1950 AEROSOLS
· ADR	AEROSOLS
· IMDG	AEROSOLS, flammable
· IATA	
· 14.3 Transport hazard class(es)	
· ADR	
	
· Class	2.1 Gases.
· Label	2.1
· IMDG, IATA	
	
· Class	2.1 Gases.
· Label	2.1
· 14.4 Packing group	
· ADR, IMDG, IATA	not regulated
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Gases.
· Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Stowage Code	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.

(Contd. on page 12)

GB

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 11)

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

· Transport category

2

· Tunnel restriction code

D

· IMDG

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Poisons Act

· Regulated explosives precursors

None of the ingredients is listed.

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

67-64-1 acetone

Listed

· Reportable poisons

None of the ingredients is listed.

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P3a FLAMMABLE AEROSOLS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H201 Explosive; mass explosion hazard.

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

(Contd. on page 13)

Safety data sheet
according to Regulation (EC) No 1907/2006, Article 31

Printing date 18.04.2024

Version number 46 (replaces version 45)

Revision: 30.03.2022

Trade name: PLASTI-KOTE QUICK DRY ACRYLIC WHITE RAL 9016 MATT 400 ML

(Contd. of page 12)

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

EUH066 Repeated exposure may cause skin dryness or cracking.

· **Classification according to Regulation (EC) No 1272/2008**

Data is based on internal technical data and technical data from suppliers.

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

GB