

## PlastiKote Trade Quick Dry Clear Lacquer 400 ml

Ord.-no.: 071003, 071004, 071005



### Technical Information

Add a durable, high-quality with Trade Quick Dry Clear Lacquer, a trade-standard clear lacquer spray paint for decoration purposes with gloss, satin, and matt finishes available. Intended for use on surfaces, treated and untreated, of wood, metal, aluminium, glass, stone, and various types of plastic. Trade Clear Lacquer Spray has a quick-drying formula that provides excellent coverage with a durable, scratch-free and wear-resistant finish. The finish is resistant to chemicals and weather influences.

#### Quality & properties

- Fast-drying
- Excellent filling property
- Lasting gloss
- Scratch free and shock proof
- Resistant to weather influences
- Corrosion preventive
- UV-resistant and non-fading
- Excellent adhesion

#### Physical & chemical data

- Base: Acrylic resin
- Colourname: Transparent
- Degree of gloss:
  - ◊ mat, 10 ±2 GU
  - ◊ semi gloss, 45 ±5 GU
  - ◊ gloss, >75 GU
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Dust dry: 5 min
- Dry to touch: 10 min
- Completely dry: 60 min
- Overcoatable: 60 min
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

