

## PlastiKote Garden 400 ml

Ord.-no.: look at ordering information

## Technical Information



Bring creativity and colour outside with PlastiKote's Garden spray paint. A multi-surface spray paint that works on wood, plastic, metal, stone and wicker, our Garden spray paint is ideal for use on outdoor furniture, planters and garden ornaments. Our water-based spray paint has an eco-friendly formula that delivers brilliant coverage and colour pay-off on any surface. Fast-drying and durable, it's ideal for anything from plant pots to trellises and gates to help add a splash of colour to your garden. Our Garden range is just one of our new, environmentally friendly paint products. With its water-based formulation, 90% less solvents and incorporating PlastiKote's Eco Technology, Garden is kinder to the home – and to the environment.

### Quality & properties

- An outdoor spray paint ideal for wood, plastic, metal, stone and wicker
- Perfect for outdoor furniture, planters and ornaments
- Available in vibrant colours
- Water-based spray paint with 90% less solvents
- With PlastiKote's Eco Technology, Garden is kinder to the home - and to the environment

### Physical & chemical data

- Base: Waterbased acrylic resin
- Colourname:
  - ◊ Willow Green
  - ◊ Surf Green
  - ◊ Herb Garden Green
  - ◊ Jamine White
  - ◊ Clotted Cream
  - ◊ Light blue
  - ◊ Sea View
  - ◊ Azalea
  - ◊ Lavender
  - ◊ Light Grey
- Degree of gloss: semi gloss, 45 ±5 GU
- Efficiency: 400 ML – 1-1,5 m<sup>2</sup>
- Dust dry: 40-60 min
- Dry to touch: 120 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: polystyrene, wood, metal, plastic, stone, wickerwork and art objects
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- pH-Value: >8
- Temperature Resistance: 80 °C
- Content:
  - ◊ 400 ML
  - ◊ 400ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labeling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 30, 2024** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)