

## PlastiKote Chalkboard 400 ml

Ord.-no.: 026001

### Technical Information



PlastiKote Chalkboard Spray Paint makes it so easy to create a fun and interactive surface, or to renovate a chalkboard, menu or scoreboard! With a non-reflective matt finish, it gives a tough, durable surface to write or draw on using chalk or chalk markers. When you're done, just clean your sprayed board off with a chalkboard eraser or a damp cloth - and if the surface ever eventually becomes worn, simply clean and add another coat. It's safe to use for kids' chalkboards and kitchen chalkboards - perfect for shopping lists, weekly food menus, reminders, and more. Plus, our new easy-spray technology gives you more control and the ability to spray from any angle. Our ultra-smooth formula provides flawless coverage that dries quickly to a tough, durable finish.

#### Quality & properties

- Quick and easy to use
- Ideal for chalkboards
- Unique Finish
- Which forms surfaces into a writable/erasable chalkboard
- Excellent coverage

#### Physical & chemical data

- Base: Alkyd resin
- Colourname: Zwart
- Degree of gloss: mat, 10  $\pm$  2 GU
- Efficiency: 400 ML – 1 m<sup>2</sup>
- Dust dry: 10-20 min
- Dry to touch: 30-40 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: chalkbord, menu and score board
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Temperature Resistance: Zwart 110 °C
- Content: 400 ML

#### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

#### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

#### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

#### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.