

PlastiKote Industrial Rust Not 500 ml

Ord.-no.: look at ordering information



Technical Information

PlastiKote Industrial Rust-Not spray paint is a rust protection spray paint, formulated for maximum rust resistance. It penetrates the surface to form a hard-wearing, permanent bond that is impact-resistant and won't peel, flake or fade for years. Available in a range of colours to match any project you might require. The formula is quick-drying and can be recoated at any time.

Quality & properties

- Fast-drying
- Re-coat at any time
- Hardwearing durable finish
- Quick and easy
- Protects from corrosion

Physical & chemical data

- Base:
 - ◊ Alkyd resin
 - ◊ Acrylic resin
- Colourname:
 - ◊ White
 - ◊ Black
 - ◊ Aluminium
 - ◊ Equipment Grey
 - ◊ Red
- Degree of gloss:
 - ◊ gloss, >75 GU
 - ◊ mat, 10 ±2 GU
 - ◊ semi gloss, 45 ±5 GU
- Efficiency: 500 ML – 2,6 m²
- Dust dry: 40-60 min
- Dry to touch:
 - ◊ 20 - 30 min
 - ◊ 120 min
- Completely dry:
 - ◊ 30-40 min
 - ◊ 2 h
- Overcoatable: 24 h
- Surfaces: Metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 3500/20 bar
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labeling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com