

PlastiKote Trade Quick Dry Acrylic 400 ml

Ord.-no.: look at ordering information



Technical Information

PlastiKote Trade Acrylic Spray Paint is a high-quality paint with a quick-drying formula. Our high-quality decorative lacquer can be used to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic. Our Trade Acrylic Spray Paint range is quick-drying, with excellent coverage, high-shine gloss and a durable finish. The final result is scratch-free and wear-resistant, and resistant to chemicals and weather. Available in different colour primers, coloured lacquers in matt and gloss finishes and clear lacquers in gloss, satin and matt.

Quality & properties

- Excellent coverage
- Lasting colour and lasting gloss
- Scratch free and wear-resistant
- Excellent vertical stability so hardly any dripping
- Resistant to chemicals and weather influences
- Excellent adhesion

Physical & chemical data

- Base: Acrylic resin
- Colourname:
 - ◊ Jet black
 - ◊ Traffic white
 - ◊ Silver grey
 - ◊ White aluminium
 - ◊ Traffic red
 - ◊ Cream
- Degree of gloss:
 - ◊ mat, 10 ±2 GU
 - ◊ gloss, >75 GU
- Efficiency: 400 ML – 1,25-1,75 m²
- Dust dry: 5-10 min
- Dry to touch: 10-20 min
- Completely dry: 2 h
- Overcoatable: 2 h
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline

1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - info-de@european-aerosols.com
European Aerosols B.V., Wolframweg 2, NL-8471 XC Wolvega - info-nl@european-aerosols.com