

## PlastiKote PURE Colours 350 ml

Ord.-no.: look at ordering information



## Technical Information

PlastiKote Pure is a revolutionary new line of water-based spray paint - a sustainable, highly pigmented, eco-friendly paint option. Designed to provide a superior, durable and long-lasting finish, it's effortlessly easy to apply and resists fading, cracking, and chipping over time. PlastiKote PURE contains over 90% less solvents, and it's completely odourless - making it safe to use both indoors and outdoors. Pure Spray Paint can be used on virtually any surface, making it the perfect choice for any painting project. PlastiKote PURE is the first of its kind to be made from sustainable and recycled materials. The Pure range comes in a can that's manufactured with 70% less CO2 impact compared to a standard can, and a 100% recycled plastic cap.

### Quality & properties

- Contains over 96% less solvents
- Odourless spray paint
- Touch dry after 30 minutes
- Recycled plastic cap
- Can produced with CO2 savings of 70%
- Suitable for toys

### Physical & chemical data

- Base: Waterbased special resin
- Colourname:
  - ◊ Charcoal
  - ◊ Flake grey
  - ◊ Signal white
  - ◊ Deep black
  - ◊ Broken white
  - ◊ Gold
  - ◊ Silver
  - ◊ Daybreak
  - ◊ Pulteney stone
  - ◊ Sandstone sandstone
  - ◊ Terracotta buff
  - ◊ Glacier drab
  - ◊ Smooth embers
  - ◊ Emerald teal
  - ◊ Indian tea
  - ◊ Loch mist
  - ◊ Sapphire pearl
  - ◊ Rapeseed
  - ◊ Forsythia
- Degree of gloss:
  - ◊ mat, 10 ±2 GU
  - ◊ gloss, >75 GU
- Efficiency: 350 ML – 0,8 - 1,2 m<sup>2</sup>
- Dust dry: 20 min
- Dry to touch: 2 h
- Completely dry: 24 h
- Overcoatable: 24 h
- Vapour pressure: 4000/20 bar
- Content: 350 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- In spite of low formation of spray mist, we recommend to protect the surrounding area.
- Shake can for 2 minutes, test spray. ATTENTION! The optimal distance is approx. 30-40 cm. Spray in 2 minute intervals several thin layers.
- PURE spray paint should not be applied during temperatures lower than 15°C, as this might delay drying time.

performance. The caps and packagings are made of recyclable material.

**Disposal**

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

**Marking/Labelling**

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 30, 2024** – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim - [info-de@european-aerosols.com](mailto:info-de@european-aerosols.com)  
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega - [info-nl@european-aerosols.com](mailto:info-nl@european-aerosols.com)