

PlastiKote Industrial Clear Acrylic 500 ml

Ord.-no.: 447795



Technical Information

PlastiKote Industrial Clear Acrylic spray paint top coat provides a tough, transparent, flexible film that is watertight, UV absorbent and will not yellow. It preserves and protects against all weather conditions, acid, alkali, and corrosion. It can be used to protect other finishes and to insulate electrical systems. And, of course, it's quick and easy to use and fast-drying. Not for use on high impact styrene, leather, Styrofoam and vinyl.

Quality & properties

- Quick and easy to use
- Fast drying
- Preserves and protects against all weather conditions, acid, alkali and corrosion
- Scratch-, shock- and impact-resistant
- Excellent gloss stability

Physical & chemical data

- Base: Nitrocellulose resin
- Colourname: Transparent
- Degree of gloss: semi gloss, 45 ±5 GU
- Efficiency: 500 ML – 2,6 m²
- Dust dry: 5-10 min
- Dry to touch: 10 -20 min
- Completely dry: 1 h
- Overcoatable: 1 h
- Surfaces: Suitable for painted surfaces. Not for use on impact resistant styrene, leather, styrofoam and vinyl
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Vapour pressure: 4000/20 bar
- Content: 500 ML

How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
- After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 30, 2024 – This release replaces all eventually earlier issued versions.