

## PlastiKote Trade Radiator Paint 400 ml

## Technical Information



PlastiKote Trade Radiator spray paint is a high-quality lacquer for embellishing and repairing radiators and central heating pipes.

Designed to make it quick and easy to paint your radiators, our Radiator spray paint is formulated to give a durable, professional and long-lasting look finish. Available in both gloss and satin finishes.

Our formula is non-yellowing and heat-resistant up to 100°C, so you can have absolute confidence with a long-lasting and attractive finish.

Best of all, there are no brushes to clean, and there'll be no brush marks left on your radiator.

**Ord.-no:** 071016, 071017

### Quality & properties

- Excellent coverage
- Lasting colour and lasting gloss
- Scratch free and wear-resistant
- Excellent vertical stability so hardly any dripping
- Excellent adhesion
- Resistant to chemicals and weather influences

### Physical & chemical data

Base: Acrylic resin  
Colourname: White  
Degree of gloss:

- gloss GU
- semi gloss GU

Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>  
Dry to touch: 3 - 4 h  
Dust dry: 40 - 60 min  
Completely dry: 24 h  
Overcoatable: 24 h  
Surfaces: radiator  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Temperature Resistance: 110 °C  
Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.  
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.  
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.  
Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.  
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.