

## PlastiKote Trade Damp Seal 400 ml

## Technical Information



PlastiKote Damp Seal spray paint is a high quality, fast drying acrylic primer to stop damp marks and other stains from spreading through to your finished surface. Based on acrylate resin, Damp Seal has excellent isolating and insulating properties

Damp Seal spray paint can be used to paint surfaces including (both treated and untreated) metal, aluminium, glass, stone and various types of plastic.

You can also use Damp Seal spray paint to stop damp and stains on mineral surfaces like plaster, as well as wood and concrete.

Can be overcoated with all dispersion varnishes and alkyd and water-based acrylic varnishes - not with 2-part lacquers.

**Ord.-no:** 071020

### Quality & properties

- Excellent isolating properties
- Excellent coverage
- Non-yellowing
- Fast-drying
- Excellent adhesion

### Physical & chemical data

- Base: Acrylic resin
- Colourname: White
- Degree of gloss: mat GU
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Dry to touch: 60 min
- Dust dry: 6 min
- Overcoatable: 60 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature Resistance: 110 °C
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the damp seal in several thin layers. Before applying the next layer, again shake the aerosol.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.