

PlastiKote Industrial High Heat Paint 400 ml

Technical Information



PlastiKote Industrial High Heat Paint has a heat-curing formula. Once cured, this spray paint forms a hard, long-lasting finish that will not burn off, chip or flake. It is ideal for any surface exposed to very high heat.

Our heat-curing formula is heat resistant up to 650°C once cured, with a durable finish that you can trust. With a high-quality and long-lasting finish, you can easily re-coat anytime as required.

Ord.-no: 002301, 002302, 002304

Quality & properties

Heat curing formula
Re-coat anytime
Heat Resistant up to 650 °C
Heat for 30 to 60 minutes (180°C)
Good flow, smooth surface

Physical & chemical data

Base: Alkyd resin
Colourname:
◦ Black
◦ White
◦ Aluminium
Degree of gloss: gloss GU
Efficiency: 400 ML – 1.75 m²
Dry to touch: 3-4 h
Dust dry: 40-60 min
Completely dry: 24 h
Overcoatable: 24 h
Surfaces: Ideal for any surface expose to very high heat
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.