

PlastiKote Trade Quick Dry Acrylic 400 ml

Technical Information



PlastiKote Trade Acrylic Spray Paint is a high-quality paint with a quick-drying formula.

Our high-quality decorative lacquer can be used to treat surfaces, treated and untreated, of wood, metal, aluminium, glass, stone and various types of plastic.

Our Trade Acrylic Spray Paint range is quick-drying, with excellent coverage, high-shine gloss and a durable finish. The final result is scratch-free and wear-resistant, and resistant to chemicals and weather.

Available in different colour primers, coloured lacquers in matt and gloss finishes and clear lacquers in gloss, satin and matt.

Ord.-no: 071008, 071009, 071010, 071011, 071012, 071013, 071014, 071015

Quality & properties

Excellent coverage
Lasting colour and lasting gloss
Scratch free and wear-resistant
Excellent vertical stability so hardly any dripping
Resistant to chemicals and weather influences
Excellent adhesion

Physical & chemical data

Base: Acrylic resin

Colourname:

- Jet black
- Traffic white
- Silver grey
- White aluminium
- Traffic red
- Cream

Degree of gloss:

- mat GU
- gloss GU

Efficiency: 400 ML – 1,25-1,75 m²

Dry to touch: 10-20 min

Dust dry: 5-10 min

Completely dry: 2 h

Overcoatable: 2 h

Surfaces: wood, metal, aluminium, glass, stone and various types of plastic

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Temperature Resistance: 110 °C

Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.