

## PlastiKote Trade Trim Paint Quick Dry 400 ml

## Technical Information



Get a truly crisp and clear finish and get the job done to the last details with PlastiKote Trade Trim Paint, a high quality lacquer for decoration purposes

Our high quality window trim spray paint is ideal for all window sills and wood trim - and it's also the first ever trade quality trim paint in spray form.

Due to the unique next gen formulation, the paint can be applied on almost all surfaces, including (treated and untreated) wood, metal, aluminium, glass, stone, and various types of plastic.

The resulting finish is long-lasting, scratch resistant and gives a durable gloss. Trim Paint comes in two different white finishes - high gloss and satinwood.

**Ord.-no:** 071006, 071007

### Quality & properties

- Fast-drying
- Excellent filling property
- Lasting gloss
- Scratch free and shock proof
- Resistant to weather influences
- Corrosion preventive
- UV-resistant and non-fading
- Excellent adhesion

### Physical & chemical data

- Base: Acrylic resin
- Colourname: White
- Degree of gloss: semi gloss GU
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Dry to touch: 30 min
- Dust dry: 10 min
- Completely dry: 2 h
- Overcoatable: 2 h
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Temperature Resistance: 110 °C
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the glue in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.