

## PlastiKote PURE Colours 350 ml

## Technical Information



PlastiKote Pure is a revolutionary new line of water-based spray paint - a sustainable, highly pigmented, eco-friendly paint option.

Designed to provide a superior, durable and long-lasting finish, it's effortlessly easy to apply and resists fading, cracking, and chipping over time.

PlastiKote PURE contains over 90% less solvents, and it's completely odourless - making it safe to use both indoors and outdoors. Pure Spray Paint can be used on virtually any surface, making it the perfect choice for any painting project.

PlastiKote PURE is the first of its kind to be made from sustainable and recycled materials. The Pure range comes in a can that's manufactured with 70% less CO2 impact compared to a standard can, and a 100% recycled plastic cap.

**Ord.-no:** 111018, 111019, 111020, 111021, 111022, 111023, 111024, 111025, 111026, 111027, 111028, 111029, 111030, 111031, 111032, 111034, 111033, 111035, 111037, 111038, 111017, 111036

### Quality & properties

Contains over 96% less solvents  
Odourless spray paint  
Touch dry after 30 minutes  
Recycled plastic cap  
Can produced with CO2 savings of 70%  
Suitable for toys

### Physical & chemical data

Base: Waterbased special resin

Colourname:

- Charcoal
- Flake grey
- Signal white
- Deep black
- Broken white
- Gold
- Silver
- Daybreak
- Pulteney stone
- Sandstone sandstone
- Terracotta buff
- Glacier drab
- Smooth embers
- Emerald teal
- Indian tea
- Loch mist
- Sapphire pearl
- Rapeseed
- Forsythia

Degree of gloss:

- mat GU
- gloss GU

Efficiency: 350 ML – 0,8 - 1,2 m<sup>2</sup>

Dry to touch: 2 h

Dust dry: 20 min

Completely dry: 24 h

Overcoatable: 24 h

Flash point:

- n.a. °C
- n.a.

Content: 350 ML

---

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

In spite of low formation of spray mist, we recommend to protect the surrounding area.

Shake can for 2 minutes, test spray. ATTENTION! The optimal distance is approx. 30-40 cm. Spray in 2 minute intervals several thin layers.

PURE spray paint should not be applied during temperatures lower than 15°C, as this might delay drying time.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.