

## PlastiKote Woodstove 400 ml

## Technical Information



PlastiKote Woodstove spray paint is just what you need to refresh your wood-burning stove or similar metal appliance. Make your stove look brand new again, with a beautiful and uniform satin sheen. Our Woodstove spray paint is exceptionally durable, giving a finish that's abrasion resistant and provides resistance against fading over time. Use our Woodstove spray paint to refresh the parts of your wood burning stove that look a bit tired or discoloured after years of use. You could also use our Woodstove spray to recolour and give a neat, professional finish to metal elements like flues, grates and more.

**Ord.-no:** 026030

### Quality & properties

- Attractive satin sheen finish
- Preserves the life of your woodstove
- Heat resistant to 800°C
- Heat for 30 to 60 minutes (180°C)
- Provides resistance against fading

### Physical & chemical data

- Base: Special resin
- Colourname: Black
- Degree of gloss: satin mat GU
- Efficiency: 400 ML – 1,5 m<sup>2</sup>
- Dry to touch: 1 h
- Dust dry: 20-30 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: Wood Stove
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.  
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.  
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.  
Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.  
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.