

PlastiKote Trade Leak Detector 400 ml

Technical Information



Trade Leak Detector spray is a convenient solution for swiftly identifying and tracing leakages in gas pipes. Crafted with a high-quality formulation, our Leak Detector spray boasts a non-combustible and non-corrosive formula that can be easily removed with water. With a simple application process, just spray the solution onto the piping to effectively pinpoint any leakages and gaps, ensuring optimal safety and reliability.

Ord.-no: 071028

Quality & properties

- Non-flammable
- Can be removed with water
- Non-corrosive
- Environment-friendly
- Slightly foaming
- Slightly basic
- High yield

Physical & chemical data

- Base: Tenside solution
- Colourname: Transparent
- Efficiency: 400 ML – 1,25-1,75 m²
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: 100 °C
- Content: 400 ML

How to use

- The aerosol should have room temperature.
- Best processing temperature 5 to 30°C.
- Before use, shake the aerosol.
- Before use, test the compatibility of the surface.
- Apply leak detector generously and allow to take effect.
- Then, remove with a tool appropriate for this purpose. When required, repeat the treatment.
- Contaminated leak detector should be regarded as chemical waste.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.