

PlastiKote Garden 400 ml

Technical Information



Bring creativity and colour outside with PlastiKote's Garden spray paint. A multi-surface spray paint that works on wood, plastic, metal, stone and wicker, our Garden spray paint is ideal for use on outdoor furniture, planters and garden ornaments.

Our water-based spray paint has an eco-friendly formula that delivers brilliant coverage and colour pay-off on any surface. Fast-drying and durable, it's ideal for anything from plant pots to trellises and gates to help add a splash of colour to your garden.

Our Garden range is just one of our new, environmentally friendly paint products. With its water-based formulation, 90% less solvents and incorporating PlastiKote's Eco Technology, Garden is kinder to the home – and to the environment.

Ord.-no: 027200, 027201, 027202, 027203, 027204, 027205, 027206, 027207, 027208, 027209

Quality & properties

An outdoor spray paint ideal for wood, plastic, metal, stone and wicker
Perfect for outdoor furniture, planters and ornaments
Available in vibrant colours
Water-based spray paint with 90% less solvents
With PlastiKote's Eco Technology, Garden is kinder to the home - and to the environment

Physical & chemical data

Base: Waterbased acrylic resin

Colourname:

- Willow Green
- Surf Green
- Herb Garden Green
- Jamine White
- Clotted Cream
- Light blue
- Sea View
- Azalea
- Lavender
- Light Grey

Degree of gloss: semi gloss GU

Efficiency: 400 ML – 1-1,5 m²

Dry to touch: 120 min

Dust dry: 40-60 min

Completely dry: 24 h

Overcoatable: 24 h

Surfaces: polystyrene, wood, metal, plastic, stone, wickerwork and art objects

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Temperature Resistance: 80 °C

Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.