

## PlastiKote SUPER Clear Sealer 400 ml

## Technical Information



Seal in a high-gloss look that lasts with PlastiKote SUPER Clear Lacquer spray paint.

Add shine with this perfect companion for your next painting project. Suitable for use on wood, metal, and more, it adds a high-gloss top coat that's tough, hard-wearing and resistant to scratches.

An excellent multi-purpose, multi-surface spray paint, SUPER Clear Lacquer is fast drying and gives a highly UV absorbent, water-resistant and rust-resistant finish that won't fade or yellow.

SUPER Clear Lacquer spray paint can be used for many types of applications, both interior and exterior.

Not for use on high impact styrene, leather, Styrofoam and vinyl.

**Ord.-no:** 011138

### Quality & properties

Multi-purpose spray paint for use on virtually any surface  
Suitable for indoors and outdoors applications  
High-grade synthetic quality  
Scratch-, bump- and impact-proof  
Resistant to weathering, light-proof, UV-resistant

### Physical & chemical data

Base: Alkyd resin  
Colourname: Transparent  
Degree of gloss: gloss GU  
Efficiency: 400 ML – 1,5 m<sup>2</sup>  
Dry to touch: 3-4 min  
Dust dry: 40-60 min  
Completely dry: 24 h  
Overcoatable: 24 h  
Surfaces: wood, metal, aluminium, glass, stone and various types of plastic  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Temperature Resistance: 110 °C  
Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.  
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.  
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.  
Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.  
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.