

## PlastiKote Plastic Primer 400 ml

## Technical Information



PlastiKote Twist & Spray Plastic Primer spray paint is ideal for renewing and decorating common household plastics, giving extra adhesion to any PlastiKote top coat. Prep your projects before applying top coats and colour to make sure you get the best colour pay-off on a smooth and durable surface.

Our Plastic Primer spray paint is perfect for both interior and exterior projects and any rigid plastic surfaces, such as patio furniture, plant pots, storage boxes, and more.

Our new Twist & Spray spray paints make painting easier than ever, with Easy-Spray technology and frustration-free features to help you get smooth, even coverage every time. Protect your fingers from sprays and splashes, and make messy paint can caps a thing of the past with our new twist & lock mechanism.

**Ord.-no:** 025606

### Quality & properties

- Provides rust protection and UV resistance
- Protects against all weather
- Multi-purpose
- Suitable for indoors and outdoors applications
- Good flow, smooth surface

### Physical & chemical data

- Base: Special resin
- Colourname: Plastic Primer
- Degree of gloss: mat GU
- Efficiency: 400 ML – 3 m<sup>2</sup>
- Dry to touch: 5 min
- Dust dry: 1 min
- Completely dry: 10 min
- Overcoatable: 10 min
- Surfaces: hard plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature Resistance: 110 °C
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.