

PlastiKote Barbecue 400 ml

Technical Information



Is your barbecue looking worse for wear after spending some time outdoors? Give it a new lease of life with a fresh coat of paint, and get ready for summer parties galore with PlastiKote BBQ spray paint.

Our barbecue-friendly spray paint offers a beautiful satin sheen that is exceptionally durable, and provides resistance against fading from wind, sun and rain. It preserves the life of metal and is abrasion-resistant, as well as being heat resistant up to 425°C.

Forget hours of fiddling with brushes - our new Twist & Spray technology gives you added control to make spray painting easier, faster and cleaner. The large, comfortable finger pad needs 35% less finger pressure than other spray paint cans. The twist and lock mechanism means there is no separate top to remove or replace after use and the cap and button design shields the finger from paint for a cleaner spray-painting process.

Ord.-no: 026020

Quality & properties

- Bring your BBQ back to life
- Provides protection against the elements
- Preserves the life of metal
- Durable and abrasion resistant
- Heat for 30 to 60 minutes (180°C)
- Heat resistant to 800°C

Physical & chemical data

- Base: Special resin
- Colourname: Black
- Degree of gloss: satin mat GU
- Efficiency: 400 ML – 1,5 m²
- Dry to touch: 1 h
- Dust dry: 20-30 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: Metal
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.