

## PlastiKote Trade Paint Remover 400 ml

## Technical Information



Remove old layers of paint quickly and easily with our Paint Remover spray - a must-have for any toolbox. PlastiKote Trade Paint Remover is a high-quality zinc spray, designed to treat galvanised and untreated steel and remove paint from paintwork, stonework, and pavement. Douse the surface for at least 15 minutes for the most effective results. Paint Remover spray paint can be used on a range of surfaces, from concrete and asphalt to stone, metal, and wood.

**Ord.-no:** 071027

### Quality & properties

- Fast-drying
- Good filling property
- Outstanding cathodic corrosion prevention
- Resistant to petrol, chemicals and weather influences
- Spot-weldable
- Excellent adhesion

### Physical & chemical data

- Base: Methylal
- Colourname: Transparent
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Content: 400 ML

### How to use

The aerosol should have room temperature.  
Best processing temperature 5 to 30°C.  
Before use, shake the aerosol.  
Before use, test the compatibility of the surface.  
Apply paint remover generously and allow to take effect. The time to take effect depends on the quality and age of the lacquer to be removed.  
Then, remove with a tool appropriate for this purpose. When required, repeat the treatment.  
Contaminated paint remover should be regarded as chemical waste.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.