

PlastiKote Industrial Upside Down Marking Paint 750 ml

Technical Information



When you need quick and easy marking, PlastiKote Upside Down Marking paint will give you bright, crisp colour with long-lasting visibility every time. Our line marking spray paint is a versatile and hardwearing paint system, designed for use in factories, car parks, building sites and sports fields.

Designed with a unique squeeze cap that gives a tight spray pattern, it minimises overspray, so you get more marking feet per can. Our Upside Down Marking paint is available in four colours that will not wash away and will resist weathering.

Suitable for high-traffic areas, our marking spray paint can be used on asphalt, grass, gravel, metal, soil and trees. With one-coat coverage, you can quickly and easily mark out parking bays, traffic signs, safety features and more. And with a non-clogging nozzle, you'll get a clean, clear line, every time..

Ord.-no: 446001, 446002, 446003, 446005

Quality & properties

- One coat coverage
- Suitable for high traffic areas
- Non-clogging nozzle
- Fast-drying
- Ideal for the industrial environments

Physical & chemical data

Base: Alkyd resin
Colourname:

- White
- Yellow
- Red
- Bleu

Degree of gloss: gloss GU
Efficiency: 750 ML – 4m² or 100-120m in length m²
Dry to touch: 30-40 min
Completely dry: 24 h
Overcoatable: 24 h
Surfaces:

- Ideal for any surface expose to very high heat
- asphalt, grass, gravel, metal, soil and trees

Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Content: 750 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.