

PlastiKote Trade Anti Slip Paint 400 ml

Technical Information



When safety and a non-slip grip are essential, PlastiKote Anti Slip spray paint is here to help. Suitable for both interior and exterior use, our special, modified, fast-drying acrylic resin lacquer spray has anti-slip particles and a transparent matt finish. Anti Slip spray paint increases grip on slippery surfaces to help reduce the risk of falls, slips, and trips - even in wet weather. Ideal for stairs, shower trays, bathroom floors, tiles around swimming pools, tool handles, and more. Expect excellent adhesion on concrete, tile, wood, metal, linoleum and most plastics.

Ord.-no: 071021

Quality & properties

- Increases the safety conditions (e.g. on stairs or bathroom floors)
- Good adhesion on concrete, asphalt, tiles, wood, metals, linoleum and most plastics
- Easy application due to an upside-down valve
- Resistant to chlorine water and saltwater
- Fast-drying
- For outdoor and indoor areas

Physical & chemical data

- Base: Acrylic resin
- Colourname: Transparent
- Degree of gloss: mat GU
- Efficiency: 400 ML – 1,25-1,75 m²
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly. The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface. The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter. Apply the anti-slip paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.