

## PlastiKote Stone 400 ml

## Technical Information



PlastiKote Stone spray paint is a textured spray that's as appealing to look at as it is to touch. Available in plenty of different finishes, from Soap Stone to Manhattan Mist, you can easily add a luxe stone look to your craft project, home interior project or DIY job.

PlastiKote Stone effect spray paint is a truly exciting and easy way to create multi-coloured textured stone effect finishes with just one can. Simply prepare the surface and spray – it's that easy. For maximum coverage and a different effect, use Satin Super under a thin coat of Stone. To enhance and preserve your Stone surface, apply Stone Clear Sealer.

Suitable for: ceramic, china, glass, metal, papier mache, stone, terracotta, wicker, and wood.

**Ord.-no:** 009436, 009439, 009440, 009444, 009445

### Quality & properties

Easy to use  
Creates multi-coloured texture stone effect  
Only for indoor use  
Various colours  
To create depth, ensure each layer is fully dried before applying the next one.

### Physical & chemical data

Base: Waterbased special resin  
Colourname:

- soap stone
- alabaster
- sante fe
- manhattan mist
- gotham grey

Degree of gloss: satin mat GU  
Efficiency: 400 ML – 1 m<sup>2</sup>  
Dry to touch: 60 min  
Dust dry: 10 min  
Completely dry: 24 h  
Overcoatable: 24 h  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Temperature Resistance: 110 °C  
Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.