

## PlastiKote Metallic 400 ml

## Technical Information



PlastiKote Metallic spray paint is ideal for small decorative and craft projects and is perfect for adding a special touch around the festive season. You can choose from a whole range of colours in our Metallic collection, from brushed nickel to antique gold. No matter what style of metal you want to recreate, you can find the effect you want with PlastiKote.

Fancy a festive project you can do in the run up to having the whole family over? Or found some old furniture and want to give it a little face lift so you can have the whole family gather round the dining table this Christmas? PlastiKote Metallic spray paint can help you out with a fabulous finish on your belongings. Just remember to check the instructions on the can before you jump onto any projects.

**Ord.-no:** 440620, 440621, 440453, 440454, 440455, 004400, 004401, 004402, 004403, 004404, 004405

### Quality & properties

- Multi-purpose
- Deep rich metallic finish
- Fast-drying
- Unique finish
- Excellent coverage

### Physical & chemical data

Base: Acrylic resin

Colourname:

- Gold
- Silver
- Copper
- Brass
- Antique Gold
- Bronze
- Flat Copper
- Brushed Nickel
- Pewter
- Graphite

Degree of gloss:

- gloss GU
- satin mat GU

Efficiency: 400 ML – 1,5 m<sup>2</sup>

Dry to touch: 10-20 min

Dust dry: 5-10 min

Completely dry: 60 min

Overcoatable: Anytime min

Surfaces:

- wood, metal, aluminium, glass, stone and various types of plastic
- range of interior and exterior decorating applications.

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Content:

- 400 ML
- 400 ml

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.