

## PlastiKote Glow in the Dark 400 ml

## Technical Information



Give a new lease of life and a fun new glow to crafts, DIY and more with PlastiKote Glow in the Dark spray paint! Our special glow in the dark spray paint will glow for up to 5 hours after exposure to light.

Glow in the Dark spray paint is perfect for crafters and hobbyists looking to add an extra dimension to their projects.

It can be used to illuminate items around the house for safety, or to add a fun extra element to toys and ornaments. Ideas for usage include light switches, kids' toys, stencilling on walls, lamp bases, garages and spooky Halloween party decorations! From stencilling stars on the ceiling to creating a garden that glows at night, this spray paint adds a luminous touch of fun to your home and craft projects. Glow in the Dark spray paint can be used on plastic, wood and metal, and on both rough and smooth surfaces.

Ord.-no: 117002

### Quality & properties

- Multi-purpose
- Can be used on virtually any surface
- Fast-drying
- Glow in the dark effect
- Unique finish

### Physical & chemical data

- Base: Acrylic resin
- Colourname: Yellow
- Degree of gloss: mat GU
- Efficiency: 400 ML – 1,5 m<sup>2</sup>
- Dry to touch: 10-20 min
- Dust dry: 5-10 min
- Completely dry: 60 min
- Overcoatable: Anytime min
- Surfaces: range of interior and exterior decorating applications.
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.