

## PlastiKote Chalkboard 400 ml

## Technical Information



PlastiKote Chalkboard Spray Paint makes it so easy to create a fun and interactive surface, or to renovate a chalkboard, menu or scoreboard!

With a non-reflective matt finish, it gives a tough, durable surface to write or draw on using chalk or chalk markers. When you're done, just clean your sprayed board off with a chalkboard eraser or a damp cloth - and if the surface ever eventually becomes worn, simply clean and add another coat.

It's safe to use for kids' chalkboards and kitchen chalkboards - perfect for shopping lists, weekly food menus, reminders, and more. Plus, our new easy-spray technology gives you more control and the ability to spray from any angle. Our ultra-smooth formula provides flawless coverage that dries quickly to a tough, durable finish.

**Ord.-no:** 026001

### Quality & properties

Quick and easy to use  
Ideal for chalkboards  
Unique Finish  
Which forms surfaces into a writable/erasable chalkboard  
Excellent coverage

### Physical & chemical data

Base: Alkyd resin  
Colourname: Black  
Degree of gloss: mat GU  
Efficiency: 400 ML – 1 m<sup>2</sup>  
Dry to touch: 30-40 min  
Dust dry: 10-20 min  
Completely dry: 24 h  
Overcoatable: 24 h  
Surfaces: chalkboard, menu and score board  
Minimum Working Temperature: 10 °C  
Maximum Working Temperature: 25 °C  
Flash point: n.a.  
Temperature Resistance: 110 °C  
Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.