

## PlastiKote Fluorescent 400 ml

## Technical Information



Turn heads with PlastiKote Fluorescent spray paint - get a high-quality, high-coverage finish for your interior and exterior decorating projects and add a pop of neon to your DIY projects or art.

Our Fluorescent spray paint is perfect for adding a dazzlingly bright finish to photo frames, furniture, decorative objects and more. With brilliant colour payoff, this paint is also great for safety applications - mark trip hazards or spots where you could bump your head.

With a wide range of bright and vivid colours, our spray paint can be used on anything from concrete and wood to glass and metal. And best of all, it's touch dry in 15-20 minutes, and totally dry after 1 hour.

**Ord.-no:** 001901, 001902, 001903, 001900

### Quality & properties

- For interior and exterior use
- Ensure instant visibility with bright day glow colours
- Easy twist & lock system
- Fast-drying
- Excellent coverage

### Physical & chemical data

- Base: Nitrocombi resin
- Colourname:
  - Yellow
  - Orange
  - Green
  - Pink
- Degree of gloss: satin mat GU
- Efficiency: 400 ML – 1,5 m<sup>2</sup>
- Dry to touch: 10-20 min
- Dust dry: 5-10 min
- Completely dry: 60 min
- Overcoatable: Anytime min
- Surfaces: wood, metal, aluminium, glass, stone and various types of plastic
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Temperature Resistance: 110 °C
- Content: 400 ML

### How to use

- Before use, carefully read the directions on the packaging and act accordingly.
- The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
- The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
- Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.