

## PlastiKote Trade Cold Zinc Primer 400 ml

## Technical Information



Supplied in a 400ml aerosol can for the smoothest and easiest application, PlastiKote Cold Zinc Primer spray paint is a spray with a zinc-based formula, based on epoxy ester. It's used for treating galvanised and untreated steel, and offers excellent cathodic corrosion prevention. Ideal for spot welding and as a weld-through primer, and heat-resistant up to 350°C. Our quick-drying formula is touch-dry in 20-30 minutes, to help speed up your work and make it easier to finish your projects.

**Ord.-no:** 071025

### Quality & properties

- Fast-drying
- Good filling property
- Outstanding cathodic corrosion prevention
- Resistant to petrol, chemicals and weather influences
- Spot-weldable
- Excellent adhesion

### Physical & chemical data

- Base: Epoxy-ester
- Colourname: Grey
- Degree of gloss: mat GU
- Efficiency: 400 ML – 1,25-1,75 m<sup>2</sup>
- Dry to touch: 30 - 40 min
- Dust dry: 10-20 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature Resistance: 350 °C
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.  
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.  
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.  
Apply the cold zinc primer in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.  
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.