

## PlastiKote Polyurethane Varnish 400 ml    Technical Information



PlastiKote Polyurethane Varnish spray paint provides a tough and durable coating to bare wooden surfaces, and protects against scratches and stains.

Available in Gloss and Satin finishes, our Polyurethane Varnish spray gives a smooth and protective finish that's non-yellowing.

Ideal for adding a high-gloss finish to wooden surfaces, you can use our high-shine Polyurethane Varnish to quickly and easily coat and protect wooden guitar bodies, upcycled furniture, and wooden crafts and DIYs. Pick the finish that's right for your project and protect it in minutes with our easy-to-use wooden varnish spray paint.

**Ord.-no:** 440591, 440592

### Quality & properties

- Hard wearing
- Non-yellowing
- Suitable for bare wooden surfaces
- Provides a tough and durable coating to bare wooden surfaces
- Protects against scratches and stains

### Physical & chemical data

- Base: Alkyd resin
- Colourname: Varnish Clear
- Degree of gloss:
  - gloss GU
  - semi gloss GU
- Efficiency: 400 ML – 1,5 m<sup>2</sup>
- Dry to touch: 3 - 4 h
- Dust dry: 40 - 60 min
- Completely dry: 24 h
- Overcoatable: 24 h
- Surfaces: wood
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Content: 400 ML

### How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

### Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

### Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

### Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

**As of May 7, 2025** – This release replaces all eventually earlier issued versions.