

PlastiKote Zinc Primer 400 ml

Technical Information



PlastiKote Zinc Primer is a high-quality zinc spray paint primer, for priming metal surfaces to resist corrosion. Perfect for priming any metal that will be at risk of corrosion, the high zinc content in our Zinc Primer spray fuses to the metal surface, protecting and sealing the surface through a unique electro-galvanic process. Suitable for use on galvanised and untreated steel. Ideal for protecting welded seams, and for coating metals like steel to keep corrosion at bay before applying a top coat of paint. Prime your projects to perfection with PlastiKote Zinc Primer's even spread and coverage. It's easier than ever to prime metal DIY projects, welding work, car detailing and more.

Ord.-no: 010599

Quality & properties

Ideal for the protection of welded seams
Resistant to highest demands against corrosion
Ideal for all metals in outside places, which are liable to rust
Weather-resistant, light-proof, UV-resistant
Quick-drying

Physical & chemical data

Base: Special resin
Colourname: Zinc Primer
Degree of gloss: satin mat GU
Efficiency: 400 ML – 1,5 m²
Dry to touch: 30 - 40 min
Dust dry: 10-20 min
Completely dry: 24 h
Overcoatable: 24 h
Surfaces: blank zinc-coated steel
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EEC in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.