

PlastiKote Glass Frosting 400 ml

Technical Information



PlastiKote Glass Frosting spray paint gives an attractive frosted finish to so many different surfaces, from windows to doors to glass cabinet fronts. Suitable for use on clear glass and plastic surfaces, Frosting is ideal for enhancing small objects around the home - fancy turning an old vase into a brand-new treasure? PlastiKote Glass Frosting spray is your answer.

Want to make the glass fronts in your kitchen cabinets opaque? PlastiKote Glass Frosting will save you from buying a whole new set of matching crockery just to save appearances!

You can even use it on windows for extra privacy, such as a downstairs loo or an upstairs bathroom that faces onto another property. You don't have to worry about putting up blinds or looking after curtains when you can use PlastiKote to give you privacy and peace of mind.

Please note: Always refer to the instructions on the reverse of the can and test an unobtrusive area before proceeding with a project.

Ord.-no: 027183

Quality & properties

- Multi-purpose
- Easy-spray technology
- Fast-drying
- Twist & Lock mechanism
- For glass and paintable transparent plastics

Physical & chemical data

- Colourname: Transparent
- Degree of gloss: mat GU
- Efficiency: 400 ML – 1,25 - 1,75 m²
- Dry to touch: 10 min
- Dust dry: 5 min
- Completely dry: 60 min
- Overcoatable: 60 min
- Minimum Working Temperature: 10 °C
- Maximum Working Temperature: 25 °C
- Flash point: n.a.
- Temperature Resistance: 110 °C
- Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.