

PlastiKote Metal Protekt 400 ml

Technical Information



PlastiKote Metal Protekt Spray Paint is a metal-protecting spray paint that gives long-lasting protection against rust and corrosion.

Like our Metal Primer sprays, Metal Protekt spray paint helps to seal out moisture and stop rust from forming, while adding a splash of colour to your project. It's suitable for use on both interior and exterior surfaces - from wrought iron gates and garden furniture to metal furniture or interior accents.

Drying time: touch dry in 10-20 minutes, thoroughly dry in 30-40 minutes.

For protection from severe rust and corrosion on surfaces that are likely to be repeatedly exposed to corrosive elements, we recommend PlastiKote Zinc Primer. Its high zinc content fuses to the metal surface, inhibiting corrosion through a unique electro-galvanic process.

Ord.-no: 001282, 001284, 001287, 001286, 001291, 001296, 001299

Quality & properties

Provides rust protection and UV resistance
Fast drying
Hard wearing
Protects against all weather influences
Quick and easy to use

Physical & chemical data

Base:

- Alkyd resin
- Acrylic resin

Colourname:

- Black
- White
- Dark Green
- Aluminium

Degree of gloss:

- gloss GU
- mat GU
- semi gloss GU

Efficiency: 400 ML – 1,5 m²

Dry to touch: 3 - 4 h

Dust dry: 40 - 60 min

Completely dry: 24 h

Overcoatable:

- 24 h
- 24 min

Surfaces: metal

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.