

PlastiKote Leaf 400 ml

Technical Information



Give a luxurious effect to your next project with PlastiKote Leaf Paint, available in Silver and Gold. Our silver and gold spray paint is perfect for picture frames, borders, Christmas decorating and more.

Our gold Leaf spray paint is a decorative, quick-drying acrylic lacquer that creates a gold leaf or silver leaf effect. Add a gleaming metal appearance with a high-gloss finish that is resistant to abrasion and scuffs, suitable for indoor or outdoor use. For use on metal, glass, ceramics, stone, wood, paper, and many other surfaces.

For optimal result, apply over a white base coat - we recommend priming with PlastiKote Twist & Spray white primer.

Our Leaf paint can be used as an under-layer paint or as an accent. Use underneath PlastiKote Chalk Sprays to create a classic looking piece of furniture. Spray and allow to dry before applying a coat of Chalk paint - the top layer of Chalk can easily be wiped back with a domestic pot scourer to reveal the Leaf below. This gives an authentic aged look, especially when used on edges and mouldings where an antique piece of furniture might have worn.

Ord.-no: 027110, 027111

Quality & properties

Fast-drying
The product can also be used underneath PlastiKote Chalk Sprays to create a classic looking piece of furniture
Available in silver and gold
As an under-laying paint or as an accent
Extremely high gloss

Physical & chemical data

Base: Acrylic resin
Colourname:

- Gold
- Silver

Degree of gloss: high gloss GU
Efficiency: 400 ML – 1,0 - 2,0 m²
Dry to touch: 10-20 min
Dust dry: 5-10 min
Completely dry: 1 h
Overcoatable: 1 h
Surfaces: metal, glass, ceramics, stone, wood, paper, carton and many other surfaces
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.