

PlastiKote Stain Sealer 400 ml

Technical Information



PlastiKote Stain Sealer spray paint is here to help you to seal and cover in stains before you paint over them. Stain Sealer covers and seals unsightly stains and water spots, and prevents water, smoke, mildew or rust stains from bleeding through. It's ideal as a spot primer for covering and sealing any stained interior surfaces before repainting with interior wall or ceiling paints.

Plus, with our new Easy-Spray Technology, you have more control to help make spray painting easier, faster and cleaner than ever. Our ultra smooth formula provides flawless coverage that dries quickly to a tough, durable finish. Our Twist and Spray cap and button design shield your fingers from paint for a cleaner spray painting process.

Ord.-no: 026010

Quality & properties

Fast-drying
Covers and seals unsightly stains and water spots
Prevents water, smoke, mildew or rust stains from bleeding through
Quick and easy
Ideal spot primer

Physical & chemical data

Base: Acrylic resin
Colourname: Stain Sealer
Degree of gloss: satin mat GU
Efficiency: 400 ML – 1-1,5 m²
Dry to touch: 5 - 10 min
Dust dry: 30 min
Completely dry: 24 min
Overcoatable: 120 min
Surfaces: Covers and seals unsightly stains and water spots
Prevents, water, smoke, mildew or rust stains from bleeding through
Minimum Working Temperature: 10 °C
Maximum Working Temperature: 25 °C
Flash point: n.a.
Temperature Resistance: 110 °C
Content: 400 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.
Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.
After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.