

PlastiKote Fast Dry Enamel Metallic 100 ml

Technical Information



Add a luxurious finish to your DIY projects, crafts, and more, with PlastiKote Fast Dry Enamel in a range of beautifully burnished metallic finishes.

Our superior quality enamel metallic spray paint comes in a handy 100ml spray, making it ideal for small upcycling projects, hobbies, or for use in arts and crafts. Suitable for use on everything from paper and cardboard, to ceramic, glass, metal, wood, and more. Our Enamel Metallic spray paint is also safe to use on children's toys and furniture. Our range of Enamel spray paints are easy to use and give great coverage, making it easy to add a polished look to your projects with a non-fading and long-lasting finish. Plus, our Fast Drying technology gives a touch-dry finish in 20-30 minutes.

Ord.-no: 001340, 001380, 001390, 001350, 001430, 001500, 001440

Quality & properties

Wide range of colours
Small can size ideal for small craft or hobby projects
Handy 100 ml size
Durable gloss
Excellent coverage

Physical & chemical data

Base: Alkyd resin

Colourname:

- red metallic
- copper
- brass
- Blue
- antique gold
- chrome

Degree of gloss: gloss GU

Efficiency: 100 ML – 0.4 m²

Dry to touch: 20 min

Dust dry: 10 min

Completely dry: 24 h

Overcoatable: 24 h

Surfaces: wood, metal, aluminium, glass, stone and various types of plastic

Minimum Working Temperature: 10 °C

Maximum Working Temperature: 25 °C

Flash point: n.a.

Temperature Resistance: 110 °C

Content: 100 ML

How to use

Before use, carefully read the directions on the packaging and act accordingly.

The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.

The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 10 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimeter.

Apply the spray paint in several thin layers. Before applying the next layer, again shake the aerosol. When desired, after drying a primer and a lacquer can be applied.

After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds).

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as "special refuse".

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of May 7, 2025 – This release replaces all eventually earlier issued versions.